Modelling of Disinfection by-products Formation via UV Irradiation of the Water from Tajan River (Source Water for Sari Drinking Water. Iran)

Allahbakhsh Javid^a, Aliakbar Roudbari^{b*}, Ahmad Reza Yari^c

^a School of Health, Shahroud University of Medical Sciences, Shahroud, Iran.

^b Center for Health-Related Social and Behavioral Sciences Research, Shahroud University of Medical Sciences, Shahroud, Iran.

^c Research Center for Environmental Pollutants, Qom University of Medical Sciences, Qom, Iran.

*Correspondence should be addressed to Dr. Aliakbar Roudbari; Email: roodbari1@yahoo.com

A-R-T-I-C-L-E I-N-F-O

Article Notes: Received: Sep 11, 2013 Received in revised form: Oct 15, 2013 Accepted: Nov 16, 2013 Available Online: Dec 25, 2013

Keywords:

Disinfection Ultraviolet radiation Modelling Drinking water-analysis Iran,Sari **A-B-S-T-R-A-C-T Background & Aims of the Study** Irradiation with ultraviolet light (UV) is used for the disinfection of bacterial contaminants in the production of potable water. The main objective of the study was to investigate and model Disinfection By-Products (DBPs) formation due to the UV Irradiation of the Tajan River water under different Irradiation conditions.

Materials & Methods: Water samples were collected throughout September 2011 to August 2013. Transportation of the sample to the laboratory was done on ice in a cooler, and physiochemical analysis was conducted immediately within one day. Dissolved organic carbon (DOC) was determined by a TOC analyzer. Irradiation experiments were conducted in a series of 25 mL glass serum bottles with Teflon septa. The present study adopts an orthogonal design. The design involved irradiation with UV at a UV/DOC ratio of 0.5–3.0 and incubating (headspace-free storage) for 5–25 sec. A 1 mM phosphate buffer maintained the pH at 6, 7, or 8 respectively, and an incubator maintained the temperature (Temp) at 15, 20, or 25 °C respectively. The development of empirical models for DBPs formation used a multivariate regression procedure (stepwise) which applied the SPSS System for Windows (Version 16.0).

Results: The results showed that the total DBPs formation ranged between 12.3 and 67.4 mg/l and that control of the levels was primarily due to the reaction time and the dissolved organic carbon level (DOC) in the water.

Conclusions: Reaction time and level of DOC concentrations in water exerted a dominant influence on the formation of DBPs during the UV irradiation of water from the Tajan River. The relationships between the measured and predicted values were satisfactory with R^2 values ranging from 0.89 (for Octanal)–0.92 (for Formaldehydes). The DOC level in water is the key factor in controlling DBPs formation.

Please cite this article as: Please cite this article as: Javid A, Roudbari A, Yari AR. Modelling of Disinfection byproducts formation via UV irradiation of the water from Tajan River (source water for Sari drinking water, Iran). Arch Hyg Sci 2013;2(4):135-142.

Background

Disinfection, as applied in water and wastewater treatment, is a process by which

pathogenic microorganisms are inactivated to provide public health protection (1). Chlorination has been the dominant method employed for disinfection for almost 100 years;

Archives of Hygiene Sciences

Volume 2, Number 4, Autumn 2013

however, it is no longer the disinfection method automatically chosen for either water or wastewater treatment because of potential problems with disinfection by-products and associated toxicity in treated water (2, 3). Among the alternatives to conventional chlorination, ultraviolet (UV) irradiation is chosen the most frequently (4).

Irradiation with ultraviolet light (UV) is used for the disinfection of bacterial contaminants in the production of potable water, and in the treatment of selected wastewater. It has a lot of advantages including no need for any chemical addition (5), fast contact times typically less than 60 sec (6,7), low capital and operating costs, simple operation with minimal system maintenance (8), and hence greater safety for operators (9). However Ultraviolet disinfection efficiency can be impeded by high levels of particulates and chemicals in water or wastewater, micro-organism aggregation, and the geometry between the UV lamp and surrounding sleeve leading to suboptimal flow paths through the lamp assembly (10,11).

A further disadvantage with UV disinfection is producing DBPs such as Octanal, Pentanal, Aldehydes and Formaldehyde, which have unfavorable effects on human and other animal's health (12,13). Other disadvantage with UV disinfection is that unlike other forms of chemical treatment it does not leave a persistent residual in the treated water, which can lead to problems of regrowth of organisms in some circumstances (14). Therefore, there is a need to gain a better understanding of the effectiveness of using UV for the disinfection of wastewater.

Most process models for UV systems are empirical in nature and do not adequately represent the distribution of UV dose that is actually delivered to micro-organisms in a continuous flow system (15). Using the published data of Nguyen, four established model forms were accessed to account for the combined effect of suspended solids and/or • Modelling of Disinfection by-products formation via ...

soluble UV absorbing compounds, and UV dose on the efficacy of disinfection. The four model forms were: a log-linear form, Davey Linear-Arrhenius, Square Root and a general nth order Polynomial form that was limited to a third order (16). Criteria for assessment of an adequate predictive mode were established including: accuracy of predicted against observed values, percent variance accounted for, and; appraisal of residuals. The Davey Linear-Arrhenius model was shown to best fit the data for UV disinfection of Escherichia Coli (ATCC 25922); followed by the nOP, log linear and Square Root forms. However, the Davey Linear-Arrhenius form must be used in conjunction with a first order chemical reaction, and was shown to predict poorly at high experimental values of UV dose (>40000 µWs cm⁻²). Davey Linear-Arrhenius model was not amenable to extrapolation beyond the observed UV dose range.

To overcome the shortcomings of the Davey Linear-Arrhenius model synthesis of two new, non-linear model forms were undertaken. The two models were a modified exponentially damped polynomial (EDP_m) and a form based on the Weibull probability distribution. The EDP_m model has three terms: a rate coefficient (K), a damping coefficient: and a breakpoint dose ([dose] B). The rate coefficient governs the initial rate of the onset of tailing. The dumping coefficient controls curvature in the survivor curve. The Weibul model has just two terms: a dimensionless scale parameter ($\beta 0$), and; a shape parameter $(\beta 1)$. The scale parameter represents the level of disinfection in the tail of the survivor curve (as $\log_{10} N/N_0$), whilst the shape parameter governs the degree of the curvature of the survivor data (17,18).

Aims of the study: In order to control DBPs formation and better monitor DBPs in the drinking water, a series of laboratory Irradiation Experiments were conducted using water from the Tajan River. Key operational parameters relating to irradiation conditions were identified

Archives of Hygiene Science	es
-----------------------------	----

Volume 2, Number 4, Autumn 2013

•Modelling of Disinfection by-products formation via ...

and multiple regression models for predicting DBPs formation were established.

Materials & Methods

Water samples were collected throughout September 2011 to August 2013. Transportation of the sample to the laboratory ice in a cooler, done on and was physiochemical analysis was conducted immediately within one day. Dissolved organic carbon (DOC) was determined by a TOC analyzer (Xangfu TOC 5000). Irradiation experiments were conducted in a series of 25 mL glass serum bottles with Teflon septa. The present study adopts an orthogonal design, which allows the variation of only one parameter at a time while other parameters maintain a designated "baseline" condition (Table 1). The design involved irradiation with UV at a UV/DOC ratio of 0.5-3.0 and incubating (headspace-free storage) for 5-25 Sec. A 1 mM phosphate buffer maintained the pH at 6, 7, or 8 respectively, and an incubator maintained the temperature (Temp) at 15, 20, or 25 °C respectively. Different DOC levels ([DOC] mg/l) of 100, 200, 300 mg/l were introduced in the water (Fabbricino & Korshin 2009). The conditions of UV/DOC=1.0 (ambient DOC concentration: 2.02 mg/l), pH=7.5 (ambient level) Temp=21°C (ambient level), were utilized as "baseline" conditions.

These glass bottles were cleaned and dried in a muffle furnace at $400^{\circ C}$ for 30 minutes prior to use. The reactions were suspended after designated reaction period by adding 12 mg ammonium chloride following USEPA method 551.1 (19). Phosphate buffer was used to maintain pH within 4.8 to 5.5. Fifty ml from each of the samples was taken for DBPs analysis. The DBPs were extracted from these 50 ml by adding 3 ml MTBE and 20g muffled sodium sulphate (20).Α solution of decafluorobiphenyl was used to achieve final surrogate concentration of 10µg/l. The use of Javid A, *et al.*/ Arch Hyg Sci 2013;2(4):135-142

decafluorobiphenyl determined the performance of the analysis. All samples were analyzed within 1 week of collection following USEPA method 551.1 (19). Two micro litres of the DBPs extracts were analyzed using gas chromatography (GC) equipped with a fused silica column (0.25mm×30m) and micro electron capture detector (μ -ECD). The standalone methodology to determine DBPs was these followed for analyses. Procedural developed using DBPs calibrations were standards. The NOM was measured as UV₂₅₄ absorption capacity at 254 nm wavelengths (UV) using an Ian 235 Spectrophotometer. The TOC and DOC were measured using a Xangfu TOC 5000A analyzer. The CO₂ detector was a linearized non-dispersive infrared detector (NDIR) (21). The organic carbon determination was made by injection mode with two injections: the first for determining total carbon and the second to find inorganic carbon. The organic carbon was then calculated as the difference between total and inorganic carbon. For DOC and UV_{254} , the samples were filtered using 0.45 µm membrane filters and then analysed (22). The pH was measured with model 200 Hatch pH Meter, which was calibrated using three point calibration (pH: 4, 7, and 10). The temperature and reaction time were adjusted in the laboratory.

Parameter Investigation:

Although 10 parameters have been identified in a number of modelling approaches, this paper focuses on the most frequently used parameters: DOC, UV254, pH, temperature and reaction time. The development of empirical models for DBPs formation used a multivariate regression procedure (stepwise) which applied the SPSS System for Windows (Version 16). The THM level was designated as the dependent variable (Y), and the parameters for the raw water quality and disinfection conditions (t, UV /DOC, pH, Temperature, [DOC⁻]) were defined as independent variables (X). The regression placed independent

Archives of Hygiene Sciences

Volume 2, Number 4, Autumn 2013

Javid A, et al./ Arch Hyg Sci 2013;2(4):135-142

variables into the equation in the order of their partial correlation coefficients (rpt) with the dependent variable, and thus the most important predictive variables Were identified via this process. Empirical equations $Y=10^{b0}X1^{b1}X2^{b2}1/4Xi^{bi}$ (equivalent to • Modelling of Disinfection by-products formation via ...

Table_	1)	Orthogonal	design	for	chlorination	experiments	of water	from	The	Tajan	<u>Ri</u> ver
Tr	eatmen	t UV/DC)C		рН	Temp(°C)	[DOC ⁻](mg/l)	Rea	ction time	e (sec)	
	1	0.5			7	20	8.5	5, 10, 15, 20, 25			
	2	1			7	20	8.5	5, 10, 15, 20, 25			
	3	1.5			7	20	8.5	5, 10, 15, 20, 25			
	4	2			7	20	8.5	5, 10, 15, 20, 25			
	5	3			7	20	8.5	5, 10, 15, 20, 25		25	
	6	1			6	20	8.5	5, 10, 15, 20, 25		25	
	7	1			8	20	8.5	5, 10, 15, 20, 25		25	
	8	1			7	15	8.5	5, 10, 15, 20, 25		25	
	9	1			7	25	8.5	5, 10, 15, 20, 25		25	
	10	1			7	20	100	5, 10, 15, 20, 25			
	11	1			7	20	200	5, 10, 15, 20, 25			
	12	1			7	20	300	5, 10	0, 15, 20, 2	25	
								-1.212			

Results

Table 2 shows the data from the irradiation experiments, and shows the DBPs formation curve in Fig 1. Octanal, Pentanal, Aldehydes and Formaldehyde are described in the following equations (1)–(4) as a function of t (5–25 sec), UV/DOC (0.5–3), pH (6–8), Temp (15–25 °C) and [DOC⁻] (8.5–300 µg/l), respectively:

Octanal = $10^{-1.111}$ (t) 0.178(UV/DOC) 0.203(pH)1.46(Temp) 0.328× ([DOC⁻]) 0.268 (R²_{adj}= 0.89, p<0.0002, n=72) (Eq.1) Pentanal = $10^{-1.203}$ (t) 0.197 (pH) 1.31(Temp) 0.279× ([DOC⁻]) 0.546 (R²_{adj}= 0.91, p<0.0002, n=72) (Eq.2) Formaldehydes= $10^{-1.278}$ (t) 0.206 (pH)1.0307(Temp) 0.299× ([DOC⁻]) 0.287 (R²_{adj}=

It shows that the total Octanal formation Eq. (1)positively correlated with all the parameters indicating the raw water quality and irradiation conditions including reaction time, pH. temperature, and DOC concentration. Pentanal and Formaldehydes formation Eq_s (2) and (3) appeared to have a positive correlation to all the independent irradiation variables but obtained no significant correlations with UV energy (UV/DOC). Finally, the Aldehydes formation Eq. (4) positively correlated to all the independent irradiation variables but negatively correlated to DOC concentration. According to the rpt values for both Octanal and Aldehydes formation models (1, 4) the reaction time (Octanal: $R_{pt}^2 = 0.364$; Aldehydes: $R_{pt}^2 = 0.299$) and the DOC concentration (Octanal: R^2_{pt} =

0.92, p < 0.0001, n = 72

Volume 2, Number 4, Autumn 2013

© 2013 Publisher: Research Center for Environmental Pollutants, Qom University of Medical Sciences. All rights reserved.

(Eq.3)

0.357; Aldehydes: $R_{pt}^2=0.392$) exerted the most $R_{pt}^2 = 0.0359$; Aldehydes: $R_{pt}^2 = 0.0285$) and UV/DOC (Octanal: $R^2_{pt} = 0.0264$; Aldehydes: $R_{pt}^2=0.0484$) while the temperature showed the $R_{pt}^2 = 0.0076;$ least influence (Octanal: Aldehydes: $R_{pt}^2=0.0132$). On the other hand, for UV/DOC independent DBPs formation (Eq. (2) and (3)), DOC concentration showed the predominant influence (Pentanal: $R^2_{pt} = 0.717$; $R_{pt}^2=0.483$) Formaldehydes: followed by (Pentanal: $R^2_{pt} =$ reaction time 0.65; Formaldehydes: $R^2_{pt}=0.210$).

The relationships between the measured and predicted values were satisfactory (Fig. 2) with R^2 values ranging from 0.89 (for Octanal)–0.94 (for Pentanal), compared with other DBPs

important influence, followed by pH (Octanal: formation models with R^2 values ranging between 0.34 and 0.99 (23, 24). This deemed these models valid to describe the experimental data. Regarding the models for Octanal and Formaldehydes, 78.6-81.8.8% of the predicted values fell within $\pm 20\%$ of the measured values with small fractions (2.23-4.01%) of extreme values (out of $\pm 31\%$ of the measured values). The models for Pentanal and Aldehydes showed relatively weak prediction ability as only approximately 59.78–64.6% of the predicted values fell within ±20% of the measured ones, whereas the extreme predicted values accounted for 10.21-11.11%.

Table 2) Mean \pm SD and range of DBPs (mg/1) from the irradiation experiments (reaction time: 5–25 se	Table 2	2) Mean ±	SD and	range of DBPs	(mg/l)	from	the irradia	ation ex	periments	reaction	time: 5-	-25 se	ec)
--	---------	-----------	--------	---------------	--------	------	-------------	----------	-----------	----------	----------	--------	-----

Treatment	Octanal	Pentanal	Formaldehydes	Aldehydes
1	7.6±3.02	4.52±1.64	1.203±0.21	3.04±0.87
	(4.58–10.62)	(2.88-6.16)	(0.99 - 1.41)	(2.17–3.91)
2	8.9 ± 4.07	4.32±1.21	1.48 ± 0.61	4.08 ± 0.98
	(4.83–12.97)	(3.11–5.53)	(0.87 - 2.09)	(3.1–5.06)
3	11.54 ± 4.6	4.42 ± 1.09	1.52 ± 0.97	4.19 ± 1.01
	(6.94–16.14)	(3.33–5.51)	(0.55-2.49)	(3.18–5.54)
	10.04.0.05	0.50.4.04	1 0	
4	10.36±3.87	3.59±1.21	1.66±0.56	4.6/±1.32
	(6.49–14.23)	(2.38–4.8)	(1.1-2.22)	(2.35–5.99)
5	149:425	6 24 1 59	1 22 0 44	4 78 + 0.00
5	(10.45, 10.15)	(4.66, 7.82)	1.22 ± 0.44	(2.70, 5.77)
	(10.45–19.15)	(4.00-7.82)	(0.76-1.00)	(3.79-3.77)
6	8 9+3 12	3 89+1 99	1 02+0 34	3 21+1 11
0	(5.78 - 12.02)	(1.9-5.88)	(0.68 - 1.36)	$(2 \ 1-4 \ 32)$
	(5.76 12.02)	(1.9 5.00)	(0.00 1.50)	(2.1 1.52)
7	14.25±6.25	5.47±2.21	0.89±0.76	6.32±2.56
	(8-20.5)	(3.26 - 7.68)	(0.13 - 1.65)	(3.76 - 8.88)
	· · · ·			
8	9.24±3.11	3.64±1.23	0.93±0.34	3.34±0.65
	(6.13–12.35)	(2.41-4.87)	(0.59 - 1.27)	(2.69 - 3.99)
9	10.49 ± 5.25	4.59±1.12	0.78 ± 0.21	5.15 ± 1.23
	(5.24–15.47)	(3.47–5.71)	(0.57 - 0.99)	(3.92–6.38)
10	8 02+3 11	687+24	1 02+0 18	6 89+2 2
10	(4.91 - 11.13)	$(4\ 47-9\ 27)$	(0.84 - 1.2)	(4.67 - 9.09)
	(1.91 11.13)	(1.17).27)	(0.01 1.2)	(1.07).07)
11	6.2±1.21	7.97±4.21	1.58±0.32	9.25±4.4
	(4.99 - 7.41)	(3.79 - 12.18)	(1.26 - 1.9)	(4.85 - 13.65)
	` '		· · · · ·	. /
12	6.8±1.25	9.12±3.11	2.01±1.74	10.23±6.01
	(5.55-8.05)	(6.01–12.23)	(0.27 - 3.75)	(4.22–13.24)

Archives of Hygiene Sciences Volume 2, Nu

Volume 2, Number 4, Autumn 2013



Figure 1) Aldehydes formation curves (temp: 15–25 °C; pH: 6–8; DOC: 8.5–300 μ g/l; UV /DOC: 0.5–3): Aldehydes =10.1t^{0.242} t (R²=0.91; p=0.0002).



Figure 2) Regressions of predicted values from multiple regressions empirical models (a-d) on the measured values (99% confidence intervals)

Archives of Hygiene Sciences	Volume 2, Number 4, Autumn	2013
© 2013 Publisher: Research Center for Environmental Pollutants, Qom Un	niversity of Medical Sciences. All rights reserved.	14(

•Modelling of Disinfection by-products formation via ...

Javid A, et al./ Arch Hyg Sci 2013;2(4):135-142



Figure 3) Effects of DOC levels on DBPs distribution

Discussion

In general, the effects of the raw water quality and irradiation conditions were expected. Higher temperatures may promote irradiation reaction rates and longer reaction time may lead to complete and higher production of DBPs (25). Generally, high DOC concentration in water provided higher inorganic precursors in the water, although additionally, types of organic material in water such as Ketones and Aldehydes an important role in determining DBPs formation (26,27). Fig. 3 shows the changes of speciation of DBPs with increasing levels of [DOC] (8.5–300 μ g/l). It appeared that with the elevation of DOC level, increased levels of DBPs were observed. The result was in agreement with research by Jin et al (2013) who indicated that the peak concentration of Aldehydes occurred at DOC concentrations of 300-500 µg/l.

Reaction time and level of DOC concentrations in water exerted a dominant influence on the formation of DBPs during the irradiation of water from the Tajan River. The relationships between the measured and predicted values were satisfactory with R^2 values ranging from 0.89 (for Octanal)–0.92 (for Formaldehydes). The DOC level in water is the key factor in controlling DBPs formation.

With knowledge of the DBPs productivity of the water, this model offers a simple and straightforward tool which can be readily applied to WTWs and distribution systems alike to provide an initial assessment of the risks of total DBPs formation at different sites, and to identify sites and systems at risk of compliance failure. Relying only on the measurement of analytically undemanding parameters, under appropriate circumstances this model offers advantages of simplicity and cost-effectiveness over other, more complex models.

Footnotes

Acknowledgments:

The authors hereby express their appreciation and thanks to Shahroud University of medical sciences.

Funding/Support:

This study was supported by Mazandaran water and wastewater company with grand no. 90/1255.

Conflict of Interest:

The authors declare no conflict of interest.

References

1. Adamowicz, W., Dupont, D., Krupnick, A. & Zhang, J. Valuation of cancer and microbial disease risk reductions in municipal drinking water: An analysis of risk context using multiple valuation methods. J Environ. Econ Manag 2011; 61(2): 213-226.

Archives of	of Hygiene	Sciences
-------------	------------	----------

Volume 2, Number 4, Autumn 2013

2. Chen BY, Westerhoff P. predicting disinfection byproduct formation potential in water. Water Res 2010; 44(13): 3755-3762.

3. Brenner A, Shacham M, Cutlip MB. Applications of mathematical software packages for modelling and simulations in environmental engineering education. Eniron Monit Assess 2005; 20(10): 1307-1313.

4. Al-Omari A, Fayyad M, AbdelQader A. Modeling trihalomethane formation for Jabal-Amman water supply in Jordan. Environ Model Assess 2005; 9(4): 245-252.

5. Amjad H, Hashmi I, Saif Ur Rehman M, Awan A, Ghaffar S. Cancer and non-cancer risk assessment of trihalomethanes in urban drinking water supplies of Pakistan. Ecotox Environ Safe 2013; 91: 25-31.

6. Chowdhury S, Champagne P, Mclellan J. Models for predicting disinfection by-product formation in drinking waters: A chronological review. Sci Total Environ 2009; 407(14): 4189-4206.

7. Chiu HF, Tsai SS, Wu TN, Yong CY. Effect modification of the association between trihalomethanes and pancreatic cancer by drinking water hardness: Evidence from an ecological study. Environ Res 2010; 110(5): 513-518.

8. Elshorbagy WE, Abu-Qadis H, Elsheamy MK. Simulation of THM species in water distribution systems. Water Res 2000; 34(13): 3431-3439.

9. Ding GY, Zhang XR, Yang MT, Pan Y. Formation of new brominated disinfection by-products during chlorination of saline sewage effluents. Water Res 2013; 47(8): 2710-2718.

10.Delarubia A, Rodriguez M, Leon VM, Prats D. Removal of natural organic matter and THM formation potential by ultra- and nanofiltration of surface water. Water Res 2008; 42(3): 714-722.

• Modelling of Disinfection by-products formation via ...

11. Fan AM. Cancer potency factor. Encycl Toxicol (Sec Ed), 2005; 401-404.

12. Goslan EH, Krasner SW, Bower M, Rocks SA, Holmes P, Levy LS. A comparison of disinfection by-products found in chlorinated and chloraminated drinking water in Scotland. Water Res 2009; 43(18): 4698-4700.

13. Francis RA, Small MJ, Vanbrrissen JM. Multivariate distributions of by-products in chlorinated drinking water. Water Res 2009; 43(14): 3453-3468.

14. Jones DB, Song H, Karanfil T. the effects of selected pre-oxidation strategies on I-THM formation and speciation. Water Res 2012; 46(17): 5491-5498.

15. Kanan A, Karanfil T. Formation of by-products in indoor swimming pool water: The contribution from filling water natural organic matter and swimmer body fluids. Water Res 2011; 45(2):926-932.

16. Hong HC, Liang Y, Han BP, Mazumder A, Wong MH. Modeling of trihalomethane (THM) formation via chlorination of the water from Dongjiang River (source water for Hong Kong's drinking water). Sci Total Environ 2007; 385(1): 48–54.

17. Kohler SJ, Buffam I, Seibert J, Bishop KH, Laudon, H. Dynamics of stream water TOC concentrations in a boreal headwater catchment: Controlling factors and implications for climate scenarios. J Hydrol 2009; 373(1): 44-56.

18. Kim JK. Fate of THMs and HAAs in low TOC surface water. Environ Res 2009; 109: 158-165.

19. Kawasaki N, Matsushige K, Komatsu K, Kohzu A, Nara FW. Fast and precise method for HPLC–size exclusion chromatography with UV and TOC (NDIR) detection: Importance of multiple detectors to evaluate the characteristics of dissolved organic matter. Water Res 2011, 45(18): 6240-6248.